

CM-700 Machine System



The **CM-700S (Standard)** and **CM-700R (Recycle)** are lean, mean, blowing machines that save you some 'green'. (cash that is). Cutting edge twin 'scalping augers', rugged design, and simple operation offers a reliable, robust machine with simple maintenance.

The "can-do" attitude of the do-it-yourself installer, or professional contractor, is realized with this little dynamo capable of performing at modest rate with **all fibers** (Cellulose, Fiberglass, Rockwool), and **all applications** (attic, dense packing, sidewall spray-on).

Need something extremely portable with low power requirements? Need a lightweight recycle machine for wall spray? We've got you covered.

What a *Cool* way to start your business.

Production Rates:

<u>Material</u> Cellulose Fiberglass Rockwool

Production Rate 431 kg/hr.

182 kg/hr.

272 kg/hr.

Optimal Performance with 'ALL' Fibers

CM-700 Standard or Deluxe



Features

Benefits:



Dual 'scalping augers enhanced fiber conditioning.

Modular control panel with plug-in receptacles.

Ball Valve bypass allows for

use as a Recycle or Standard

machine.

maintenance.



Quick release dual augers for easy airlock

CM-700R 'Recycle'

Quick release hopper for easy handling.



Specifications:

•Weight: 82 kg.

- Dimensions:
- •71 cm l x 56 cm w x 147 cm h
- •Hopper Capacity: 0.21 m³
- •Airlock size: 20.3 cm dia. x 25.4 cm long 0.28 bar w/ 6.3 cm output tube. •Drive motor: 1/3 h.p
- •Blower:
- •4.7 amp. /3 m³/min. (Standard)
- •7 amp. /4 m³/min. (Deluxe)
- Power Requirements: •8 amp. single input (Standard)
- •10 amp. single input (Deluxe)

Machine Options

- 15.25 cm dia. wheel package (pictured) • Hopper extension w/ loading tray (0.24 m³ total) (pictured)
- Deluxe w/45 m 3-postion remote control cord & 7 amp. variable speed blower • CE conformity f/export









Hopper Chute accomodates

most generic size trash bins.

Gas Vacuums

Questions? Call us at 419-232-4871